


APPLICATION : In TVs, CFL, electronic ballast, automobile, telecommunication, audio & instrumentation.

TECHNICAL DETAILS

- Dielectric** : Polypropylene
- Electrodes** : Foil
- Ref. Standard** : Q/320684DER01-2001
- Encapsulation** : Epoxy dip coated (IPD)
- Flame Retardancy** : Conforming to UL 94 V-0
- Environmental** : 55/105/21
- Category**
- Capacitance** : ± 5 %, ± 10 %
- Tolerance**
- Test Voltage** : 2.5 x Vr (5 secs.)
- Tan δ** : ≤ 0.008 at 1kHz
- I. R.** : C ≤ 0.33 mfd : > 3.0 X 10⁴ MΩ , C > 0.33 mfd : > 10⁴ MΩ



Dimensions (max. in mm) :

L	P	d
6.5	4.0	0.5
7.0	4.5	0.5
7.5	5.0	0.5
8.0	5.0	0.5
9.0	6.0	0.5
9.5	6.0	0.5
10	6.0	0.5
11	7.0	0.5
12	7.0	0.5
13	8.0	0.6
14	9.0	0.6
15	9.0	0.6

Capacitance mfd.	630 VDC			1000 VDC		
	L	B	H	L	B	H
0.00022	6.0	4.0	12.0	6.5	5.0	12.5
0.00027	6.0	4.0	12.0	6.5	5.0	12.5
0.00033	6.0	4.0	12.0	6.5	5.0	12.5
0.00039	6.0	4.0	12.0	6.5	5.0	12.5
0.00047	6.0	4.0	12.0	6.5	5.0	12.5
0.00056	6.0	4.0	12.0	6.5	5.0	12.5
0.00068	6.0	4.0	12.0	6.5	5.0	12.5
0.00082	6.5	4.5	12.0	7.0	5.5	13.0
0.0010	6.5	4.5	12.0	7.0	5.5	13.0
0.0012	7.0	5.0	12.0	8.0	6.0	14.0
0.0015	7.5	5.0	12.0	8.5	6.0	14.0
0.0018	7.5	5.0	12.0	8.5	6.0	14.0
0.0022	8.0	5.5	12.0	9.0	6.0	14.0
0.0027	8.0	5.5	13.0	9.0	6.5	14.0
0.0033	9.0	5.5	13.0	9.0	6.5	15.0
0.0039	9.5	5.5	13.0	9.5	7.0	15.0
0.0047	9.5	5.5	13.0	10.0	7.5	15.5
0.0056	9.5	5.5	14.0	10.0	7.5	16.0
0.0068	9.5	7.0	14.0	12.0	8.0	17.0
0.0082	11.0	7.0	15.0	13.0	8.5	17.0
0.010	11.0	8.0	15.0	13.0	8.5	17.0
0.012	12.0	8.0	16.0	13.0	8.5	18.0
0.015	12.0	8.0	16.0	14.0	9.0	19.0
0.018	12.0	8.0	19.0	14.0	9.0	19.0
0.022	12.0	8.0	19.0	14.0	9.0	19.0
0.027	14.0	8.0	21.0			
0.033	14.0	8.0	21.0			
0.039	16.0	9.5	22.0			
0.047	16.0	9.5	22.0			