




METALLISED POLYPROPYLENE CAPACITORS

MPD SERIES

APPLICATION : In hum-free, step type Electronic Fan Regulator. Premium Quality long life capacitors, with normal features.

TECHNICAL DETAILS

- Dielectric** : Polypropylene
- Electrodes** : Vacuum deposited zinc-aluminium
- Voltage** : 250 VAC
- Ref. Standard** : IEC 384-16
- Encapsulation** : Epoxy dip coated (MPD)
- Flame Retardancy** : Conforming to UL 94 V-0
- Environmental** : 55/105/56
- Category**
- Capacitance** : $\pm 10 \%$
- Tolerance**
- Test Voltage** : 415 VAC
- I. R. at 100 V** : $\geq 30,000$ secs.
- Dissipation factor** : $\leq 2.5 \%$ at 100 kHz



L	P	d
30	27.5	0.8

Dimensions (max. in mm) :

Capacitance mfd .	250 VAC		
	L	B	H
1.0	30	6.5	16.0
1.2	30	7.0	16.5
1.5	30	8.0	17.0
1.8	30	8.5	18.0
2.0	30	9.0	18.5
2.2	30	10.0	19.5
2.4	30	10.5	18.5
2.5	30	11.0	19.0
2.7	30	12.0	19.5
3.0	30	12.0	20.0
3.2	30	13.5	20.0
3.3	30	14.0	20.5
3.4	30	14.0	20.0
3.5	30	14.5	20.5
3.7	30	15.0	21.0
3.8	30	15.0	21.0
4.0	30	16.0	21.5
4.2	30	16.0	21.5
4.5	30	16.0	22.5
4.7	30	16.5	23.0



ISO 9001

DESAI ELECTRONICS PVT. LTD.

870/5, Bhandarkar Institute Road, Pune : 411 004.

Ph. : 91-20-25654553, 25654554. Fax : 25654273. e-mail : mktg@deccapactors.net